




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61N 1/00	A2	(11) International Publication Number: WO 00/33913 (43) International Publication Date: 15 June 2000 (15.06.00)
(21) International Application Number: PCT/US99/29037 (22) International Filing Date: 8 December 1999 (08.12.99) (30) Priority Data: 60/111,347 8 December 1998 (08.12.98) US (71) Applicant: STRATEGIC BUSINESS DEVELOPMENT, INC. [US/US]; 3576 Kaweonui Road, Princeville, HI 96722 (US). (72) Inventor: FRY, Stephen, M.; 3576 Kaweonui Road, Princeville, HI 96722 (US). (74) Agents: MUSICK, Eleanor, M. et al.; Brown, Martin, Haller & McClain, 1660 Union Street, San Diego, CA 92101-2926 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: SYSTEM AND METHOD FOR STIMULATION AND/OR ENHANCEMENT OF MYOCARDIAL ANGIOGENESIS

(57) Abstract

Shock-waves are applied using a combination lithotripsy probe/balloon system, comprising a needle and cannular balloon which can be inserted through the skin at a point between the ribs into the cavity beneath the chest wall and overlying the heart. Alternatively, the shock-wave can be administered extracorporally or via a catheter. A fluid injector is connected to the balloon, allowing it to be inflated with saline or other appropriate fluid to fill the space (for transmission of shock waves and/or to displace tissue - such as lung) and contact the surface of the heart. A shock-wave (acoustic) generator is used to generate shock-waves through the lithotripsy probe, through the fluid and into the myocardial tissue. The fluid provides a uniform medium for transmission of the acoustic energy, allowing precise focus and direction of the shock-wave to induce repeatable cavitation events, producing small fissures which are created by the cavitation bubbles. In this case, channels would not be 'drilled' into the heart muscle, minimizing trauma to the tissue while still creating conditions that will stimulate increased expression of angiogenic growth factors.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SYSTEM AND METHOD FOR STIMULATION AND/OR ENHANCEMENT OF MYOCARDIAL ANGIOGENESIS

RELATED APPLICATIONS

5 This application claims priority to United States Provisional Application Serial No. 60/111,347, filed December 8, 1998, the disclosure of which is incorporated herein in its entirety.

BACKGROUND OF THE INVENTION

10 Coronary artery disease ("CAD") is a leading cause of death worldwide. More than 6 million Americans have CAD, of which some 1.5 million suffer heart attacks (myocardial infarction), resulting in 500,000 deaths and nearly 1 million hospitalizations annually in the U.S. CAD is characterized by narrowing of the arteries that feed the heart muscle ("myocardium"); without adequate
15 blood supply, the tissue becomes starved for oxygen ("ischemic"), and the heart does not pump as efficiently. A heart attack (which usually indicates a complete blockage of a coronary artery) can result in a portion of the heart muscle being ischemic for a prolonged time and then dying, which can permanently reduce the patient's ability to perform exercise, such as walking. The treatment of CAD
20 includes preventive measures (modification of diet and/or exercise, reduction in hypercholesterolemia through various drugs, etc.), minimally invasive clearing of arteries (angioplasty, atherectomy, intravascular stenting), and surgical bypass of the diseased artery(ies) (coronary artery bypass surgery, "CABG"). While preventive measures have helped to reduce the number of CAD patients, CAD
25 remains one of the greatest health problems in the world today.

 Angioplasty and related catheter-based procedures can unblock some arteries, but the blockages, or "stenoses", typically return, a condition known as "restenosis," within 6-18 months due to intimal hyperplasia, which is creation of scar tissue from the traumatic vessel wall damage during the angioplasty
30 procedure. The use of stents (metal or polymer tubes or coils which hold the artery open) has decreased the restenosis rate by about one half. Radioactive devices (catheters and stents) are being developed to further reduce the

restenosis rate. However, angioplasty has fundamental limitations, which are unlikely to ever be solved completely. These include inability to reach smaller vessels, morbidity associated with failed angioplasty procedures, poor success rate in certain vessels, e.g., saphenous vein grafts, and general inability to
5 completely revascularize the heart muscle (myocardium). Approximately 800,000 coronary angioplasty procedures are performed annually in the U.S.

Coronary artery bypass procedures are performed on approximately 400,000 people in the U.S. annually, and nearly 800,000 people worldwide. Although the primary result of CABG is generally satisfactory, the saphenous
10 veins used in most patients become blocked 10-15 years after surgery. Also, CABG procedures are very traumatic, and carry a risk of mortality around 1-3%. Although "heart port", "off-pump", and other minimally invasive types of CABG procedures are being developed, they are all quite invasive and/or utilize a pump and oxygenator ("heart-lung machine"), which introduces additional
15 trauma to the patient.

Transmyocardial revascularization (TMR) using a laser (sometimes referred to as TMLR, LTMR, PMR, PTMR, or DMR) has been developed over the past decade, initially by a company called PLC Systems, Inc., of Franklin, Massachusetts. PLC's system utilizes a high power (800-1000 W) carbon
20 dioxide (CO₂) laser which drills small channels in the outside (epicardial) surface of the myocardium in a surgical procedure. The holes communicate with the left ventricle, which delivers blood directly to the heart muscle, mimicking the reptilian heart. Many other companies are developing laser TMR systems, most introducing the laser light via optical fibers through a flexible catheter, making
25 the procedure less-invasive. These companies include Eclipse Surgical Technologies, Inc., of Sunnyvale, California, and Helionetics, Inc., of Van Nuys, California. The Eclipse TMR system uses a Ho:YAG laser with a catheter-delivered fiber optic probe for contact delivery to the myocardium. The Helionetics system is based on an excimer laser. In addition to the
30 holmium:YAG and excimer lasers, and other types of lasers have been proposed for TMR.

While the channels created during TMR are known to close within 2-4 weeks, most patients tend to improve clinically over a period of 2-6 months. Such clinical improvement may be demonstrated by reduction in chest pain ("angina"), and a dramatic increase in exercise tolerance ("ETT", or treadmill test). The mechanism of laser TMR is not fully understood, but it is postulated that the laser causes near-term relief of angina through denervation or patent channels, with subsequent long-term clinical improvement due to angiogenesis, i.e., growth of new blood vessels, mainly capillaries, which perfuse the heart muscle. These new "collateral" vessels enable blood to reach downstream ("distal") ischemic tissues, despite blockages in the coronary arteries. Some of the possible mechanisms by which the laser induces angiogenesis could include activation of growth factors by light, thermal, mechanical, cavitation or shockwave means. In fact, all lasers which have been successfully used for TMR are pulsed systems, and are known to create shock waves in tissue, and resulting cavitation effects.

Cavitation can be induced in a liquid-rich environment like tissue. An opening or cavity can be created in a fluid by thermal vaporization or an rapid movement of a solid through the liquid (such as explosive expansion of a gas bubble formed in the tissue). When energy is focused into a small area of a liquid in a short time, e.g., < 1 ms, the temperature can rapidly rise above boiling temperature and vapor is formed. Typically, the vapor volume is over 1000 times the original liquid volume. The vapor is formed at very high pressure and an explosive vapor bubble will be created, rapidly expanding to equalize the internal bubble pressure to ambient pressures. This bubble creates an opening in the liquid (or tissue) environment. While the bubble is expanding, the temperature inside will decrease and drop below the boiling point. The vapor then turn backs into liquid. Due to the momentum of expansion however, the bubble expands, further creating a semi-vacuum. At some point, the negative pressure overcomes the momentum of expansion, and the process becomes an implosion. Like the expansion, the implosion can be very fast, inducing a high momentum in the surrounding liquid. The motion of the liquid during implosion

will be spherically symmetric, concentrated in the middle of the imploding bubble. The collision at the moment of total implosion is very forceful and is capable of creating supersonic density waves in the liquid, or "shock-waves." If the energy release at the start of bubble formation is also very concentrated, a shock-wave can also be generated at the very start of the bubble.

Cavitation bubbles can also be formed by focusing shock waves into the liquid/tissue from an external shock wave generator. Shock-wave generators create locally very high temperatures inducing plasmas in liquids. The heat transfer to the environment subsequently creates a vapor bubble inducing the process as described above.

Another method to induce cavitation effects in liquid is by displacing the liquid at high speed by moving a solid object through the liquid. Because a delay occurs before the liquid can fill in the gap behind the object moving through the liquid, a vacuum will briefly form. The liquid filling this vacuum will be accelerated to very high speeds. At the instant the gap is filled, the liquid collides within the center of the gap, forming a shock-wave. In tissue environment, cells are sucked from their matrix by the rapidly moving liquid causing the tissue itself to effectively become liquefied.

Catheters have been previously developed which can deliver high intensity ultrasound energy to the coronary arteries for the purpose of removing thrombus (blood clots) and/or atherosclerotic plaque (see, e.g., U.S. Patent No. 5,524,620 of Rosenschein) [note that these catheters are quite different from the intravascular imaging devices that use low intensity ultrasonic signals to probe and image arterial cross-sections]. These catheters could be modified to deliver ultrasound energy to the myocardium.

Catheters have also been previously developed which can remove tissue via spark erosion, electrical discharge, or other shock wave producing technologies. These shock waves, if of sufficient amplitude in a localized region, can create a cavitation effect. This is the principle behind shock-wave lithotrippers, which are used to non-invasively break-up kidney and ureteral stones ("calculi"). Such systems are known in the art (particularly in the fields of

urology and gastroenterology), but can produce severe tissue damage – typically much greater than the damage produced by laser TMR.

Initially, TMR was performed on patients who were not acceptable candidates for angioplasty or bypass surgery. It is hoped that TMR could be a replacement for bypass surgery, for those patients who's arteries continue to restenose after angioplasty. Ultimately, with a non-invasive TMR approach as described herein, TMR could be used on CAD patients instead of (or prior to) angioplasty, CABG or any other revascularization procedure. In addition to the possibility of the TMR procedure replacing conventional revascularization procedures, it is currently being used as an adjunct to CABG surgery; in this case, areas of the myocardium where blood flow cannot be completely restored using surgical bypass (e.g., because the vessels are too small or too clogged) can be treated with TMR, enhancing the blood flow to these distal regions, and improving the overall outcome of the CABG procedure.

In parallel with laser TMR developments have been developments of angiogenic growth factors, which can also stimulate small capillary growth ("angiogenesis") in heart muscle. Vascular endothelial growth factor ("VEGF"), angiopoietin-1 and -2, basic fibroblast growth factor (bFGF), and other growth factors are now being studied, with therapeutic angiogenesis being demonstrated in animal models. A few studies have progressed to testing on humans. Although it is too early to make a definitive conclusion, it appears that angiogenesis created by these growth factors may help CAD patients clinically. However, the administration of these drugs, once they are approved by the FDA, will either be systemic – opening the potential for unwanted vessel growth, for example in the eye or in tumors; or they may require direct introduction of the growth factor(s) into the myocardium. Therefore, companies are developing devices for injecting growth factors into heart muscle, including lasers, catheter-based systems, and other devices.

Current technologies for revascularizing the heart – including all commercialized TMR approaches to-date – have severe limitations. Laser TMR systems are very expensive (\$250,000-500,000). The original (PLC) system requires open chest surgery, which is nearly as traumatic as CABG surgery.

Some catheter-based TMR systems have recently been approved by the FDA, but they are also expensive (\$250,000 or more for the laser, and \$1000 or more for the catheter). Catheter-based systems may also require a guidance technique, such as electrical mapping, which introduces further costs.

5 The development of growth factors, and the delivery of genes or proteins which introduce or activate specific growth factors is ongoing. Many growth factors are combined with a recombinant adenovirus to provide an efficient gene delivery vector for a variety of cell types and tissues. However, the long-term complications of the use of these adenoviral vectors, e.g., cancerous growths,
10 and systemic effects, e.g., viral infection, are currently unknown. If direct targeting to the myocardium is required, catheter-based systems may be necessary. Some of these catheter systems even utilize an expensive laser to make channels or pockets, where the drug is injected.

 While the mechanism of action of TMR is not fully understood, it must
15 rely on one of several possible effects of pulsed lasers: light, heat, and/or shock waves (and resulting cavitation). Neither light nor heat has previously shown any ability to improve the condition of CAD patients, although various surgical instruments using heat have been used for decades in heart surgery. Therefore, the most likely characteristic of laser energy which could cause angiogenesis is
20 the cavitation resulting from shock waves produced by explosive vaporization of tissue using high power pulsed laser systems.

 As cavitation phenomena appear to be the likely source of trauma which stimulates expression of natural growth factors responsible for myocardial angiogenesis, a rational and cost-effective approach to TMR would be to select
25 an appropriate shock wave generator, and a delivery system that can utilize these shock waves to create cavitation in the myocardium. The laser may not be the best candidate for this function. Lasers produce both shock waves and heat, and heat has often been found to be 'bad' for the heart (e.g., thermal angioplasty). Lasers also usually represent the most expensive technology that
30 can provide a given physical result, and current TMR systems are not cost-effective (hospitals are currently paying \$500,000 for a laser to generate shock waves that could also be obtained using a \$50,000 electromechanical generator system).

 Studies using focused ultrasound for TMR were first reported by Smith
35 and Hynynen in 1998. (*Ultrasound in Medicine & Biology*, Vol. 24, No. 7, 1998,

pp. 1045-1054.) Ultrasonic transducers were used to deliver focused ultrasound energy to animal myocardium. The authors speculate that, potentially, a phased array of transducers could be used to focus shock waves into human hearts (around or between the ribs) completely non-invasively. Mechanisms of achieving the desired results in the experimental animals included tissue destruction via thermal vaporization or cavitation. However, while a completely non-invasive procedure would be a significant advantage, this should not come at the cost of diminished effectiveness. Access to the heart by transmission of shock waves to produce cavitation is limited to a relatively small area of the myocardium. Shock waves cannot be focused effectively through tissues of different densities, such as bone, or through air spaces (e.g., lungs or thoracic cavity). Furthermore, since the energy must pass through inhomogeneous tissues (i.e., tissues of varying density, such as bone), the ultrasonic waves may be non-uniformly diffracted, refracted and/or reflected, resulting in possible variation in the focus or other distortion of the beam which may prevent the shock waves from causing cavitation. Shock waves also must be transmitted through a liquid or solid material, and are not effectively transmitted through air spaces, such as in the lungs or thoracic cavity. Therefore, it becomes extremely difficult to treat a sufficient area of myocardium to generate the desired angiogenic result to improve clinical outcome. In TMR procedures, where many traumatic sites must be created (typically, channels on the order of 1 mm are typically made), repeatability is an important issue. Thus, while the concept of using focused ultrasound for TMR has been shown feasible in an animal laboratory, a number of issues must be addressed before ultrasound or other shock wave (cavitation) approaches can be made to be safe and effective for TMR in actual human patients. Accordingly, the need remains for relatively inexpensive surgical, minimally invasive, and non-invasive systems for performing TMR.

SUMMARY OF THE INVENTION

It is the object of this invention to provide system and method for revascularizing the heart utilizing cavitation effects to trigger and enhance angiogenesis in the myocardium.

It is further an object of this invention to induce such cavitation effects using either surgical or minimally invasive methods, either by a percutaneous, endoscopic or catheter-based device.

In an exemplary embodiment, the transcutaneous application of shockwaves is achieved using a combination lithotripsy probe/ balloon system, comprising a needle and cannular balloon which can be inserted through the skin at a point between the ribs into the cavity beneath the chest wall and
5 overlying the heart. A fluid injector is connected to the balloon, allowing it to be inflated with saline or other appropriate fluid to fill the space (for transmission of shock waves and/or to displace tissue – such as lung) and contact the surface of the heart. A shock-wave (acoustic) generator is used to generate shock-waves through the lithotripsy probe, through the fluid and into the myocardial tissue.
10 The fluid provides a uniform medium for transmission of the acoustic energy, allowing precise focus and direction of the shock-wave to induce repeatable cavitation events, producing small fissures which are created by the cavitation bubbles. In this case, channels would not be ‘drilled’ into the heart muscle, minimizing trauma to the tissue while still creating conditions that will stimulate
15 increased expression of angiogenic growth factors. The fluid in the balloon also stabilizes the myocardium, reducing variations which can occur do to movement of the heart as it beats, since the balloon remains in contact with the surface of the heart throughout the procedure. Visualization of the target area can be achieved using known methods including an integrated shock wave
20 generating/transmitting endoscope or a separate optical or video-based viewing endoscope.

In another exemplary embodiment, a transcutaneous endoscopic probe has a transducer disposed at its distal end which is inserted through a small incision between the ribs, such as in CABG procedures ("midcab"), so that the
25 distal end is in contact with the heart. A small fluid-inflatable balloon may be disposed at the distal end of the endoscope, outside of the transducer, so that the balloon is positioned between the transducer and the exterior surface of the heart, or the transducer may contact the heart directly. As in the previous embodiment, the saline or other fluid in the balloon couples the shock-waves
30 generated by a shock-wave generator to the myocardium, providing more precise focusing of the energy. In an alternate embodiment, the transducer is located in the proximal end of the endoscope, with the shock-wave conducted to the distal tip using an appropriate transmission wire.

In yet another embodiment, a laser is coupled to an optical fiber which
35 extends coaxially through a flexible catheter or flexible/rigid endoscope. A

metal cap disposed at the tip of the catheter converts the optical energy into shock-wave energy, by inducing rapid tip motion to create highly localized cavitation effects. The distal end of the catheter (or endoscope) may include a fluid-filled balloon as in the previous embodiments to couple the shock-wave
5 directly to the myocardium.

In still another embodiment, an extracorporeal lithotripsy device is used to direct focused shock-waves toward the myocardium. A fluid-filled balloon is inserted percutaneously into the space between the inner wall of the chest and the heart to conduct the shock-wave to the heart through a uniform medium.

10 The system and method of the present invention can also be utilized to augment conventional cardiac surgical procedures. For example, endoscopic cavitation system can be used to induce angiogenesis to initiate improved collateral circulation as an enhancement to, and/or backup for, bypass grafts. Alternatively, a miniaturized surgical ultrasonic cavitation system can be utilized
15 to intra-operatively produce 1 mm channels in myocardium during a CABG procedure. Testing of such a system (Verdaasdonk, Cobelens – University Hospital Utrecht, The Netherlands) has demonstrated that the channels produced in this fashion are essentially identical (in terms of myocardial histology) to laser-produced TMR channels.

20 A shock-wave generator which has been used to induce cavitation effects for treatment of human disease is the extracorporeal shock wave lithotripsy ("ESWL") system commonly used for breaking up kidney or ureteral stones. These systems generally utilize a spark device and reflector to create a focused shock wave that penetrates tissue and impinges at great amplitude on the stone
25 to be fractured by a combined shock-wave and cavitation effect. Smaller, and more focused systems are currently being developed in Europe for treatment of joints. The region of shock waves could be potentially controlled by the focusing reflector, leading to a larger area of myocardium receiving shockwaves/cavitation effects more uniformly than could be achieved via a laser
30 TMR system.

An important aspect of the invention is that the shock waves are transmitted and focused only through tissue, water, or some other solid/liquid medium. Air spaces between the skin and the myocardium will preclude delivery of shock waves. In addition, shock waves travel differently in harder
35 tissues, such as bone, and could be defocused by traveling through the ribs.

Some implementations of the present invention utilize a fluid-filled balloon, inserted via needle, between the ribs, inflated, and utilized to transmit the shock waves to the myocardium. The shock-waves are applied to the balloon using minimally-invasive or entirely non-invasive methods, relying on the density
5 uniformity provided by the fluid to conduct the shock wave energy to a localized region within the heart tissue.

As with laser TMR systems, it may be desirable to synchronize the shock wave with the heartbeat to occur at a specified phase (e.g., T-wave) of the beat. However, with sufficiently small amplitude shock waves, such synchronization
10 may not be required. Various embodiments of the present invention may be utilized, incorporating synchronization or not. However, unlike the laser TMR systems, the amplitude of the shock wave delivered to the myocardium can be varied over a wide range with an extracorporeal shock wave system; this may allow cumulative doses of shock waves sufficient to induce angiogenesis, while
15 further minimizing the myocardial tissue effects of the treatment.

As it has recently been found that certain proteins may modulate the effect of vascular growth factors, e.g., the angiopoietins, ANG-1 and ANG-2, another aspect of the present invention involves the combined use of these growth factor modulators and low-amplitude shock wave treatment using a
20 system as previously described. While delivery of genes to upregulate expression of various growth factors could be performed simultaneously with the modulators, it may be desirable to first deliver the modulators, and then at a later time to stimulate growth factors. In this case, a non-invasive (or percutaneous – with shock wave transmitting balloon inserted via needle) approach would be
25 preferable to catheter-based delivery of another agent into the myocardium.

BRIEF DESCRIPTION OF THE DRAWINGS

Understanding the present invention will be facilitated by consideration of the following detailed description of preferred embodiments of the present
30 invention taken in conjunction with the accompanying drawings, in which like numerals refer to like parts and in which:

Figure 1 is a diagrammatic view of a first embodiment of a system according to the present invention;

Figure 2 is a diagrammatic view of a second embodiment of the present
35 invention;

-11-

Figure 3 is a diagrammatic view of a third embodiment of the present invention; and

Figure 4 is a diagrammatic view of a hand-held embodiment of the invention.

5

DESCRIPTION OF PREFERRED EMBODIMENTS

Each embodiment of the present invention utilizes a shock-wave generator of the type used for extracorporeal lithotripsy procedures, which generators are well known in the art. One such system is disclosed in U. S. Patent No. 5,031,626 of Hassler, et al., where the shock wave generator has a planar circular membrane consisting of electrically conductive material. One side of the membrane is in contact with the propagation medium in the housing, and the opposite side of the membrane is covered by an insulating layer. A planar coil with spiral windings is disposed on the same side of the membrane, with the insulating 5a therebetween. The coil is connected via terminals to a high voltage pulse generator, by means of which the coil is charged with high voltage pulses. When the coil is charged with a high voltage pulse, the membrane abruptly moves away from the coil due to the effect of the magnetic field generated by the coil. As a result of this movement of the membrane, a pressure pulse is introduced into the propagation medium in the interior of the housing, and as it passes through the propagation medium, it is transformed into a shock wave. The shock wave propagates in the direction of a center axis of the shock wave generator.

An alternative source of the shock-wave can an opto-acoustic transducer such as that described in U.S. Patent No. 5,944,687 of Benett, et al. The transducer is located at the end of an optical fiber which may be located within a catheter or other probe device. Energy for operating the transducer is provided optically by laser light transmitted through the optical fiber to the transducer. Pulsed laser light is absorbed in the working fluid of the transducer to generate a thermal pressure and consequent adiabatic expansion of the transducer head such that it does work against the ambient medium. The transducer returns to its original state by a process of thermal cooling. The motion of the transducer within the ambient medium couples acoustic energy into the medium. By pulsing the laser at a high repetition rate an ultrasonic radiation field can be established locally in the medium. The preceding descriptions are intended to

-12-

be exemplary of the prior art as relates to shock-wave generating apparatus, and is not intended to limit the scope of the invention in any way.

As shown in Figure 1, a first embodiment of the present invention illustrated a percutaneous implementation comprising a shock-wave generator 2
5 connected to a lithotripsy probe 4 adapted for insertion through a small incision in the chest wall 10, between ribs 12. Probe 4 is configured as a needle/
cannular balloon system constructed in a manner similar to conventional balloon catheters and other devices used for angioplasty, hyperthermal treatment of
tumors, and other medical procedures. The general construction for a balloon
10 device is provided in U.S. Patent No. 5,368,591 of Lennox, et al., which describes a heated balloon catheter. In the present invention, the heating wires are replaced with shock-wave transducers or transmission wires. A
polyethylene terephthalate (PET) balloon is mounted on nylon shaft. The balloon should be large enough to expand to fill the thickness of the space between the
15 inner chest wall and the heart. The wall thickness of balloon is about 0.001 inch. For use in a catheter, a guidewire, which extends past the distal end of the catheter, may be used to guide the catheter through the vascular system or
luminal structure.

In the present invention, the delivery device includes a cannula
20 containing a trocar for making a puncture in the chest wall and balloon 6 at the distal tip of the cannula which can be inflated with fluid to fill the space between the inner chest wall and the myocardium. Balloon 6 is fillable with an
shock-wave transmissive fluid such as normal saline (0.9 percent NaCl in water). Syringe 8 provides means for controlling the inflation and deflation of balloon 6
25 via tubing connected to an inlet in balloon 6. The exterior of balloon 8 is preferably coated with a non-stick coating having a low coefficient of friction, such as silicone or polysiloxane.

Balloon 6 is inflated (e.g., with saline) to take up the space and contact the surface of the beating heart 14. Shock waves from the generator 2 and probe
30 4 are focused through the saline solution in balloon 6, as indicated by waves 16. Fluid-filled balloon 6 couples shock waves 16 to the myocardium, reducing hemolysis which could occur if the shock waves are transmitted through blood and potentially allowing more refined focusing than would be available, if the catheter contacted the myocardium directly.

As shown in Figure 2, an endoscopic probe 24 could also be the shock wave coupler, where the shock waves are created by external (extracorporeal) generator 22. Probe 24 is inserted through an incision 28 in the chest wall 30 between ribs 32. The shock-waves can be communicated to the distal end of probe 24 by way of a transmission wire. Alternatively, electrical energy generated by generator 22 is transmitted through a wire to the distal end of the endoscope to create a spark at a metallic cap. The response of the metal to the spark creates shock waves and/or cavitation effects. A flexible saline- or gel-filled sac or balloon 26 is located at the distal tip of probe 24 to contact the myocardium of heart 34 and transmit the shock waves. Visualization of the target area can be achieved using known methods. A video-based viewing endoscope 36 is illustrated in the figure as a separate device, but may be incorporated into the endoscope using methods known in the art.

In an alternate embodiment, the cavitation effect is induced by ultrasonic vibration of a tip disposed at the distal end of the endoscope in an assembly similar to that disclosed in U.S. Patent No. 4,223,676, of Wuchinich, et al., which is incorporated herein by reference. In that patent, an apparatus for the surgical removal of tissue is disclosed comprising a handpiece having a resonant vibrator with a magnetostrictive stack composed of a nickel alloy sandwich and a connecting body encompassing a hollow elongated tool which is ultrasonically vibrated at its tip longitudinally to a peak-to-peak stroke of at least 0.005 inches at about 25 KHz. A generator powers the vibrator and is automatically controlled at the frequency to maintain the resonant vibration. As applied to the present invention for treatment of cardiac disease, the tip, which is preferably titanium, has a distal diameter on the order of 1 mm, is solid, rather than hollow as disclosed in the '676 patent. The shape of the tip is selected to distribute its mass to maintain resonant vibration and will typically be tapered, having a larger diameter at its proximal end than at its distal end.

Such an ultrasonic needle device can be used in a manner similar to that disclosed relative to Figure 2 except that it would be used to drill holes into the myocardium during open chest surgery or during minimal invasive CABG or thorascopic procedures. The cavitation effects at the needle tip provide a mechanism to dissolve muscular tissue and create channels in the myocardium similar to laser channels. The diameter of the channels would typically be up to 1 mm diameter.

Figure 4 illustrates an exemplary structure for a hand-held probe 60 having resonant stack 62, metal connector 64, which is formed from a material having a high characteristic acoustic impedance or an alloy such as monel. The connector is partially housed in housing 66. The resonant stack 62 is excited by electrical power provided by the generator, such as that generally referred to as the shock-wave generator in Figures 1 and 2. Connector 64 connects to tip 68 to transmit the resonant vibration to distal end 70 which is can be placed in direct contact with the myocardium or can have a fluid-filled balloon interposed between the distal end 70 and the myocardium to conduct the vibration to the tissue. The frequency of the vibration is selected to induce cavitation in the tissue, and may be used to form the channels through the myocardium that are normally associated with TMR. To avoid trauma, it may be preferable to avoid generation of the channels, and rely upon the cavitation effect to provide the therapeutic effect.

A device using the vibrating tip can be used transcutaneously as described relative to the embodiment of Figure 2, or used as a hand-held tool in an open chest surgical procedure, where the surgeon has a clear view of the heart and can physically position the tip at desired locations on the myocardium. Viewing in either case may be enhanced by using an endoscopic viewing device incorporated in the probe. Such a hand-held system has the advantage of providing tactile feedback, so that the surgeon can feel how much pressure is being applied. This provides a significant advantage over laser TMR systems, which have no mechanism by which tactile feedback could be obtained.

In the embodiment illustrated in Figure 3, using the laser-based method for inducing shock waves previously described, laser 42 is coupled to an optical fiber which extends coaxially through a flexible catheter 44. The catheter is inserted using standard procedures through the femoral artery 48, up through aorta 50 across the aortic valve and into the left ventricle of heart 52, where it contacts the inner wall. A metal cap 46 disposed at the tip of the catheter converts the optical energy into shock-wave energy, by inducing rapid tip motion to create highly localized cavitation effects. The distal end of the catheter (or endoscope) may include a fluid-filled balloon 48 as in the previous embodiments to couple the shock-wave directly to the myocardium.

The laser approach could also be used with an endoscopic probe for use in minimally invasive CABG procedures. In this case, due to the wider available

distal surface of the endoscopic probe, a phased array of shock wave generators could be placed to appropriately focus or direct the shock waves to the myocardium. Multiple shock-wave generators could be created using multiple fibers directed toward the same or different distal tip elements. Other means for
5 generating shock-waves can be used, including electric spark methods, which are known in the art.

The system and method of the present invention can also be utilized to augment conventional cardiac surgical procedures. For example, endoscopic cavitation system can be used to induce angiogenesis to initiate improved
10 collateral circulation as an enhancement to, and/or backup for, bypass grafts.

An important aspect of the invention is that the shock waves are transmitted and focused only through tissue, water, or some other solid/liquid medium. Air spaces between the skin and the myocardium will preclude delivery of shock waves. In addition, shock waves travel differently in harder
15 tissues, such as bone, and could be defocused by traveling through the ribs. the present invention makes use of a delivery system that conducts the shock-waves to the heart tissue to induce cavitation either by a mechanical device, i.e., endoscope, catheter, needle, or vibrating tip, or by ensuring a uniform transmission media between the point from which the shock wave emanates and
20 the heart. Some implementations of the present invention utilize a fluid-filled balloon, inserted via needle, between the ribs, inflated, and utilized to transmit the shock waves to the myocardium. The shock-waves are applied to the balloon using minimally-invasive or entirely non-invasive methods, relying on the density uniformity provided by the fluid to conduct the shock wave energy to
25 a localized region within the heart tissue.

It may be desirable to synchronize the shock wave with the heartbeat to occur at a specified phase (e.g., T-wave) of the beat, using techniques known to those of skill in the art. However, with sufficiently small amplitude shock waves, such synchronization may not be required. Various embodiments of the
30 present invention may be utilized, incorporating synchronization or not. However, unlike the laser TMR systems, the amplitude of the shock wave delivered to the myocardium can be varied over a wide range with an extracorporeal shock wave system; this may allow cumulative doses of shock waves sufficient to induce angiogenesis, while further minimizing the
35 myocardial tissue effects of the treatment.

It will be apparent to those skilled in the art that various modifications and variations can be made in the system and method of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modification and variations of this invention
5 provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A system for treatment of coronary disease comprising:
a generator for producing a shock wave for inducing a cavitation effect in heart tissue; and
5 a delivery system for transmitting shockwaves from the generator to the heart tissue.
2. The system of Claim 1, wherein the generator comprises an extracorporeal shock wave lithotripsy system.
3. The system of Claim 1, wherein the generator comprises an electrical
10 power source and a transducer disposed at a distal end of the delivery system and the delivery system includes a connector for providing electrical power from the power source to the transducer.
4. The system of Claim 3, wherein the delivery system further comprises a delivery device selected from the group consisting of an endoscope, an
15 extracorporeal lithotripsy probe, a hand-held surgical probe, and a catheter.
5. The system of Claim 4, wherein the delivery system further comprises a fluid-inflatable balloon disposed at a distal end of the delivery device and a means for inflating and deflating the balloon.
6. The system of Claim 1, wherein the generator comprises an electrical
20 power source and a transducer, and the delivery system comprises a shock-wave transmitting connector connected to the transducer and extending through to a distal end of one of an endoscope, a lithotripsy probe, a hand-held surgical probe, and a catheter.
7. The system of Claim 6, wherein the delivery system further comprises a fluid-inflatable balloon disposed at a distal end of the shock-wave transmitting
25 connector and a means for inflating and deflating the balloon.
8. The system of Claim 7 wherein the fluid-inflatable balloon is inflated using a saline solution.
9. The system of Claim 1, wherein the generator comprises an electrical
30 spark generator and a metal cap, and the delivery system comprises:
a wire connected at a proximal end to the spark generator and at a distal end to the metal cap; and
a device for manipulating a position of the metal cap selected from the
35 group consisting of an endoscope, a lithotripsy probe, a hand-held surgical probe, and a catheter.

10. The system of Claim 9, wherein the delivery system further comprises a fluid-inflatable balloon disposed at a distal end of the manipulating device and a means for inflating and deflating the balloon.

5 11. The system of Claim 10 wherein the fluid-inflatable balloon is inflated using a saline solution.

12. The system of Claim 1, where the generator comprises a laser and an electro-optical transducer for converting laser light into a shock-wave and the delivery system comprises:

10 an optical fiber extending from an output of the laser to the electro-optical transducer; and

a manipulating device selected from the group consisting of an endoscope, a lithotripsy probe, a hand-held surgical device, and a catheter for retaining the optical fiber therein.

15 13. The system of Claim 10, wherein the delivery system further comprises a fluid-inflatable balloon disposed at a distal end of the manipulating device and a means for inflating and deflating the balloon.

14. The system of Claim 13 wherein the fluid-inflatable balloon is inflated using a saline solution.

20 15. The system of Claim 1 further comprising means for introducing one or more growth factor modulators either systemically or locally to the heart tissue.

16. A system for treating heart disease in a patient comprising:

an extracorporeal shock-wave generator;

a device for coupling shock-waves from the generator to an outer chest wall of the patient; and

25 a needle/cannula-balloon device for coupling shock-waves from the coupling device to the myocardium comprising:

a cannula;


a shock-wave transmitting connector;

a fluid-inflatable balloon;

30 a channel within the cannula for transmitting fluid to the balloon.

17. The system of Claim 16, further comprising a channel for introducing at least one growth factor modulator.

18. A system for treating heart disease in a patient comprising:
a hand-held shock-wave generator probe having an elongated portion for
extending through a chest wall of the patient and to the myocardium;
a shock-wave generator connected to the probe.
- 5 19. The system of claim 18, further comprising a visualization device
incorporated in the probe.
20. The system of claim 18, wherein the probe comprises a vibrating tip for
contacting the myocardium to induce cavitation effects.
21. A method of treating heart disease in a patient comprising:
10 inserting a delivery device between the chest wall and the heart for
transmitting shock-waves;
coupling the delivery device to a shock-wave generator;
applying shock-waves to the myocardial tissue.
22. The method of Claim 21, wherein the step of inserting a delivery device
15 further comprises introducing a shock-wave conducting fluid into a fluid-
inflatable balloon.
23. The method of Claim 22, wherein the conducting fluid is a saline
solution.
24. The method of Claim 21, further comprising synchronizing the step of
20 applying shock-waves with the patient's heartbeat.
22. The method of Claim 21, further comprising, before or during application
of shock-waves, introducing at least one growth factor modulator.
23. The method of Claim 21, wherein the step of inserting the delivery device
comprises inserting at least one transcutaneous device selected from the group
25 consisting of a needle, a cannula, a hand-held probe, and an endoscope.
24. The method of Claim 21, further comprising targeting the shock-waves
using a fluoroscopy system.
25. The method of Claim 21, further comprising targeting the shock-waves
using an electrical mapping system.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 June 2000 (15.06.2000)


PCT

(10) International Publication Number
WO 00/033913 A3

- (51) International Patent Classification⁷: **A61N 7/00**
- (21) International Application Number: PCT/US99/29037
- (22) International Filing Date: 8 December 1999 (08.12.1999)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/111,347 8 December 1998 (08.12.1998) US
- (71) Applicant: **STRATEGIC BUSINESS DEVELOPMENT, INC.** [US/US]; 3576 Kaweonui Road, Princeville, HI 96722 (US).
- (72) Inventor: **FRY, Stephen, M.**; 3576 Kaweonui Road, Princeville, HI 96722 (US).
- (74) Agents: **MUSICK, Eleanor, M.** et al.; Brown, Martin, Haller & McClain, 1660 Union Street, San Diego, CA 92101-2926 (US).
- (81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- (88) Date of publication of the international search report:
8 May 2003

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR STIMULATION AND/OR ENHANCEMENT OF MYOCARDIAL ANGIOGENESIS



(57) Abstract: Shock-waves are applied using a combination lithotripsy probe/balloon system, comprising a needle and cannular balloon which can be inserted through the skin at a point between the ribs into the cavity beneath the chest wall and overlying the heart. Alternatively, the shock-wave can be administered extracorporeally or via a catheter. A fluid injector is connected to the balloon, allowing it to be inflated with saline or other appropriate fluid to fill the space (for transmission of shock waves and/or to displace tissue - such as lung) and contact the surface of the heart. A shock-wave (acoustic) generator is used to generate shock-waves through the lithotripsy probe, through the fluid and into the myocardial tissue. The fluid provides a uniform medium for transmission of the acoustic energy, allowing precise focus and direction of the shock-wave to induce repeatable cavitation events, producing small fissures which are created by the cavitation bubbles. In this case, channels would not be 'drilled' into the heart muscle, minimizing trauma to the tissue while still creating conditions that will stimulate increased expression of angiogenic growth factors.

WO 00/033913 A3

WO 00/033913 A3



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/29037

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61N7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61N A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	WO 98 51224 A (NITA HENRY) 19 November 1998 (1998-11-19) the whole document ---	1,3-7, 18,20 2,8,10, 11,13-17
X A	US 5 827 203 A (NITA HENRY) 27 October 1998 (1998-10-27) column 2, line 14-43 column 4, line 6-47 column 8, line 24-28 ---	1,3,4,6, 18-20 2,16
X A	WO 98 16157 A (ETHICON ENDO SURGERY INC) 23 April 1998 (1998-04-23) page 4, line 2-16 page 6, line 22 -page 7, line 9 --- -/-	1,3,4,6, 18,20 2,16



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

° Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

12 April 2000

Date of mailing of the international search report

19/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Grossmann, C.

INTERNATIONAL SEARCH REPORT

Internal Application No
PCT/US 99/29037

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	WO 97 39691 A (UNIV CALIFORNIA ;BENETT WILLIAM (US); CELLIERS PETER (US); DASILVA) 30 October 1997 (1997-10-30) page 2, line 34 -page 3, line 15 page 4, line 17 -page 5, line 2 ----	1-4,12, 18,20 5-8,10, 11,13-17
X A	WO 90 09762 A (GEN HOSPITAL CORP ;PHYSICAL SCIENCES INC (US)) 7 September 1990 (1990-09-07) the whole document ----	1,2,9 16,18,20
A	EP 0 834 287 A (INTERVENTIONAL TECHNOLOGIES) 8 April 1998 (1998-04-08) column 2, line 33 -column 4, line 16 -----	1,5,7,8, 10,11, 13,14, 16,18

INTERNATIONAL SEARCH REPORT

Int. application No.
PCT/US 99/29037

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 21-25
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by therapy
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

information on patent family members

Intern: Application No
PCT/US 99/29037

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9851224 A	19-11-1998	US 5989208 A AU 7378198 A EP 0983030 A	23-11-1999 08-12-1998 08-03-2000
US 5827203 A	27-10-1998	NONE	
WO 9816157 A	23-04-1998	US 5989274 A AU 4756597 A AU 5080498 A EP 0932365 A WO 9816154 A	23-11-1999 11-05-1998 11-05-1998 04-08-1999 23-04-1998
WO 9739691 A	30-10-1997	US 5944687 A AU 2809997 A EP 0902654 A	31-08-1999 12-11-1997 24-03-1999
WO 9009762 A	07-09-1990	AT 133050 T AU 637786 B AU 5190990 A DE 69024949 D DE 69024949 T DK 460069 T EP 0460069 A ES 2081367 T IL 93494 A JP 6014936 B JP 4503175 T US 5425735 A US 5281231 A US 5246447 A	15-02-1996 10-06-1993 26-09-1990 29-02-1996 05-09-1996 18-03-1996 11-12-1991 01-03-1996 26-05-1995 02-03-1994 11-06-1992 20-06-1995 25-01-1994 21-09-1993
EP 0834287 A	08-04-1998	US 5800450 A AU 3994597 A BR 9704681 A CA 2209367 A JP 10113349 A	01-09-1998 09-04-1998 12-01-1999 03-04-1998 06-05-1998